

# BFGoodrich® DR444

Take control mile after mile with this long-lasting, rain-fighting highway and regional drive tire.



## GOES THE DISTANCE

### Seriously long-lasting tire

- 28/32nds tread depth for long tread life
- Tread design and unique compounding created to help you go the distance.



## SERIOUS GRIP

### Bring on the rain

- Tread design equipped to help improve traction on the road.
- Large central grooves help to evacuate water and increase wet traction.



## RETREADABILITY COMES STANDARD

### Multiple lives

- All steel construction for excellent retreadability.



Application	Highway	Regional	Urban	Coach/ Bus	On/ Off-Road
Position	Steer	Drive	Trailer		

■ Recommended Application

**5 YEAR** <sup>(3)</sup>  
5 Year / 2-Retread Manufacturer's  
Limited Casing Guarantee

Size	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed (1)		Loaded Radius		Overall Diameter		Overall Width (2)		Approved Wheels (Measuring wheel listed first)	Min. Dual Spacing (2)		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
				mph	km/h	in.	mm.	in.	mm.	in.	mm.		in.	mm.		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	77081	28	75	120	19.4	493	41.8	1062	11.2	284	8.25, 7.50	12.5	318	497	6175	105	2800	720	5840	105	2650	720
11R22.5	H	98035	28	75	120	19.4	493	41.8	1062	11.2	284	8.25, 7.50	12.5	318	497	6610	120	3000	830	6005	120	2725	830
275/80R22.5	G	90375	28	75	120	18.9	480	40.6	1032	10.9	277	8.25, 7.50	12.2	311	511	6175	110	2800	760	5675	110	2575	760
11R24.5	G	52321	28	75	120	20.5	521	43.9	1116	11.0	279	8.25, 7.50	12.5	318	472	6610	105	3000	720	6005	105	2725	720
11R24.5	H	89861	28	75	120	20.5	521	43.9	1116	11.0	279	8.25, 7.50	12.5	318	472	7160	120	3250	830	6610	120	3000	830
275/80R24.5	G	55617	28	75	120	19.5	495	41.9	1064	10.6	269	8.25, 7.50	12.2	311	500	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.

(1) Exceeding the lawful speed limit is neither recommended nor endorsed.

(2) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

(3) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer. See [www.bfgoodrichtrucktires.com](http://www.bfgoodrichtrucktires.com) for more information. BFGoodrich® tires are subject to a continuous development program. BFGoodrich® Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligation.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit [www.bfgoodrichtrucktires.com](http://www.bfgoodrichtrucktires.com) for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.