

BFGoodrich® ST230

Take control in and out of the city with this curb-fighting, smooth-wearing steer/all-position regional tire that's SmartWay® verified.



FIGHTS IRREGULAR WEAR

Smooth, even-wearing tread

- 1900 miniature tread sipes help to resist irregular wear.
- Solid shoulders help to resist irregular wear in high scrub environments.



CONQUERS THE CURBS

Bump and bruise resistant

- Curb guards help protect sidewalls against most impacts and abrasions for long casing life.



RETREADABILITY COMES STANDARD

Multiple lives

- All steel construction for excellent retreadability.



Application	Highway	Regional	Urban	Coach/ Bus	On/ Off-Road
Position	Steer	Drive	Trailer		

■ Recommended Application ■ Acceptable Application

5 YEAR ⁽³⁾
5 Year / 2-Retread Manufacturer's
Limited Casing Guarantee

Size	Load Range	Catalog Number	Tread Depth 32nds	Max. Speed (1)		Loaded Radius		Overall Diameter		Overall Width (2)		Approved Wheels (Measuring wheel listed first)	Min. Dual Spacing (2)		Revs Per Mile	Max. Load Per Tire Single				Max. Load Per Tire Dual			
				mph	km/h	in.	mm.	in.	mm.	in.	mm.		in.	mm.		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
225/70R19.5	G	74208	15	75	120	14.8	376	32.1	815	9.2	233	6.00, 6.75	10.0	254	647	3970	110	1800	760	3750	110	1700	760
10R22.5	G	62086	17	75	120	18.6	472	39.8	1012	10.0	255	7.50, 6.75, 8.25	11.4	288	521	5675	115	2575	790	5355	115	2430	790
11R22.5	H	68045	18	75	120	19.1	486	41.1	1043	11.1	282	8.25, 7.50	12.5	318	505	6610	120	3000	830	6005	120	2725	830
255/70R22.5	H	95971	17	75	120	17.1	435	36.6	929	10.2	258	8.25, 7.50	11.6	295	566	5510	120	2500	830	5070	120	2300	830
275/80R22.5	G	50614	18	75	120	18.6	472	40.0	1016	10.9	277	8.25, 7.50	12.2	311	518	6175	110	2800	760	5675	110	2575	760
315/80R22.5 ⁽⁴⁾	L	55458	17	75	120	19.6	499	42.4	1077	12.5	317	9.00, 9.75	13.8	351	489	9090	130	4125	900	8270	130	3750	900
11R24.5	H	79184	18	75	120	20.2	513	43.3	1100	11.0	279	8.25, 7.50	12.5	318	478	7160	120	3250	830	6610	120	3000	830
275/80R24.5	G	71892	18	75	120	19.2	488	41.3	1049	10.6	269	8.25, 7.50	12.2	311	503	6175	110	2800	760	5675	110	2575	760

Note: Wheel listed first is the measuring wheel.

(1) Exceeding the lawful speed limit is neither recommended nor endorsed.

(2) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly.

(3) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer. See www.bfgoodrichtrucktires.com for more information.

(4) Not approved for use with an 8.25 wheel.

BFGoodrich® tires are subject to a continuous development program. BFGoodrich® Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligation.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit www.bfgoodrichtrucktires.com for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.